


TURBOCORD®

Sandblast hose



Marking:  Turbocord® - Diameter - PN 12 bar - Abrieb/Abrasion 60/70 mm³

Norm	EN ISO 1307:2008, ISO 4649 (previous DIN 53516)	Abrasion value tube	60-70 mm ³
Working pressure	12 bar	Construction tube	Smooth
Bursting pressure	36 bar	Color tube	Black
Min. temperature	-30 °C	Compound cover	SBR
Max. temperature	+80 °C	Cover	Fabric finish
Electr. resistance tube	Electrical conductive <10 ⁶ Ω	Color cover	Black
Electr. resistance cover	Antistatic <10 ⁹ Ω	Reinforcements	Textile plies
Compound tube	NR/SBR		

Art.-no.	Ø Inner (mm)	Wall (mm)	Ø Outer (mm)	Weight (kg/mtr)	Length (mtr)
3500013027	13,0	7,0	27,0	0,575	40
3500019033	19,0	7,0	33,0	0,750	40
3500025039	25,0	7,0	39,0	0,840	40
3500032048	32,0	8,0	48,0	1,100	40
3500038054	38,0	8,5	55,0	1,450	40
3500042060	42,0	9,0	60,0	1,700	40
3500050070	50,0	10,0	70,0	2,150	40

Application: High quality classic sandblast hose which, due to its extreme abrasive resistant tube, is suitable for transporting extremely abrasive materials such as quartz sand, blasting grit, corundum, glass etc. The special extruded tube ensures a very long lifespan compared to other products available on the market. The Turbocord sandblast hose is one of the bestsellers in the sand blasting industry.

Remark:

- Cutted length possible

