


ARIACORD®/DIN

Air pressure/water hose



Marking:  Ariacord® PN 10/16 DIN 20018 - year - BP 40 bar

Norm	DIN 20018, EN ISO 1307:2008	Construction tube	Smooth
Max. working pressure air	10 bar	Color tube	Black
Max. working pressure water	16 bar	Compound cover	SBR
Bursting pressure	40 bar	Cover	Fabric finish
Min. temperature	-30 °C	Color cover	Black
Max. temperature	+70 °C	Resistance cover	Ageing resistant, Weather resistant
Compound tube	SBR	Reinforcements	Textile plies

Art.-no.	Ø Inner (mm)	Wall (mm)	Ø Outer (mm)	Bending radius (mm)	Weight (kg/mtr)	Length (mtr)
3220032000	32,0	8,0	48,0	220	1,330	40
3220035000	35,0	8,0	51,0	220	1,450	40
3220038000	38,0	6,0	50,0	280	1,110	40
3220042000	42,0	9,0	60,0	260	1,930	40
3220050000	51,0	7,0	65,0	400	1,730	40
3220053000	53,0	10,0	73,0	350	2,530	40
3220075000	76,0	10,0	96,0	500	3,490	40

Application: Standardized, high quality, extra robust, thick walled flexible hose for medium duty applications in industry, maintenance workshops, tunnel construction, infrastructure and on construction sites. Suitable for transport of water and air. The hose is also resistant to oil mist.

Remark:

- Cutted length possible
- Dimensions 38, 51 and 76 are not mentioned in the DIN 20018

We recommend assembly with

5560
Safety clamps



5611
Swiveling flange

