

CARBOFORM®/EN/ISO

Oil and fuel resistant hose



Marking: Carbopump® Marine Fuel Hose ISO 7840:2013 A1 E10/B10 compatible - CE - SAE J 1527:2011 USCG A1 - RINA - LLOYD'S Register - year- DN

Norm	EN ISO 1307:2008, ISO 7840:2013-A1	Cover	Fabric finish
Min. temperature	-20 °C	Color cover	Black
Max. temperature	+80 °C	Resistance tube	Biodiesel, E10
Compound tube	Synthetic rubber	Aromatic content maximum	50 %
Construction tube	Smooth	Resistance cover	Flame resistant, Self extinguishing
Color tube	Black	Reinforcements	Textile plies
Compound cover	Synthetic rubber		

Art.-no.	Ø Inner (mm)	Wall (mm)	Ø Outer (mm)	WP (bar)	BP (bar)	Weight (kg/mtr)
3305006000	6,0	4,5	15,0	3	14	0,240
3305008000	8,0	4,0	16,0	3	14	0,250
3305010000	10,0	4,0	18,0	3	14	0,280
3305012000	12,0	4,5	21,0	3	10	0,360
3305016000	16,0	4,5	25,0	3	10	0,450
3305019000	19,0	4,5	28,0	3	10	0,500

Application: Fuel supply hose for leisure boats up to max. 24 meters long. Suitable for transport of oil, unleaded petrol and fuels with an aromatic content up to 50%. Also suitable for E10 and biodiesel.

Remark:

- Cutted length possible
- Coils in various lengths.

