

VAPORCORD®/ALIM/EXTRA

Food resistant discharge and cleaning hose



Marking: Vaporcord®/Alim/Extra - Steamhose / Dampfschlauch Hot Water PN .. bar max. 100°C / Steam PN 6 bar max. 164°C - EG1935/2004 - BFR XXI Kat. 2 - FDA CFR 21 § 177.2600

| | | | |
|-------------------------------|--|-------------------|---|
| Norm | BfR XXI:2002 (cat. 2), EN ISO 1307:2008, EU 1935/2004, FDA (CFR 21 § 177.2600) | Construction tube | Smooth |
| Max. operating pressure steam | 6 bar | Color tube | White |
| Bursting pressure steam | 60 bar | Compound cover | Modified elastomer |
| Min. temperature | -35 °C | Color cover | Blue |
| Max. temperature hot water | +100 °C | Resistance tube | Up to max. 15% alcohol |
| Max. temperature steam | +164 °C | Resistance cover | Animal fat, Poultry fat, Vegetable fats |
| Compound tube | NBR | Reinforcements | Textile plies |

| Art.-no. | Ø Inner (mm) | Wall (mm) | Ø Outer (mm) | Max. WP hot water (bar) | BP (bar) | Bending radius (mm) | Cover | Weight (kg/mtr) | Length (mtr) |
|------------|--------------|-----------|--------------|-------------------------|----------|---------------------|---------------|-----------------|--------------|
| 3406010000 | 10,0 | 4,5 | 19,0 | 30 | 90 | 55 | Smooth | 0,290 | 40 |
| 3406013000 | 13,0 | 5,0 | 23,0 | 30 | 90 | 65 | Smooth | 0,430 | 40 |
| 3406019000 | 19,0 | 6,0 | 31,0 | 30 | 90 | 100 | Smooth | 0,600 | 40 |
| 3406025000 | 25,0 | 6,0 | 37,0 | 30 | 90 | 125 | Smooth | 0,800 | 40 |
| 3406032000 | 32,0 | 7,0 | 46,0 | 20 | 60 | 195 | Fabric finish | 1,100 | 40 |
| 3406038000 | 38,0 | 8,0 | 54,0 | 20 | 60 | 250 | Fabric finish | 1,600 | 40 |
| 3406050000 | 50,0 | 8,0 | 66,0 | 20 | 60 | 350 | Fabric finish | 1,800 | 40 |

Application: Suitable for transport of liquid foodstuffs such as milk and milk products, various juices, vegetable and animal fats and oils. The hose can also be used as a low pressure steam hose for cleaning purposes in kitchens, slaughterhouses, food processing factories etc. Very flexible and therefore extremely suitable for reel applications. The outer wall is resistant to animal, vegetable and poultry fats. After use, drain water or steam and let the hose dry in a proper way. This significantly reduces the risk of popcorning of the inner wall.

Remark:

- Cutted length possible
- Drain the hose after usage
- Please pay attention to the cleaning instructions which you can find in the footer of our homepage

We recommend assembly with

5430
Steam couplings



5410
Boss steam couplings



5420
Boss steam couplings

