

## TUBIMAR®/LLOYDS

### Marine wet exhaust hose



Marking: Scamo/SP® Marine wet exhaust LLOYD'S Register nr. 96/00127(E4) RINA nr. DIP061008CS - 20/03/08 SAE J 2006:03 R2 - ISO 13363:04 Type 2 CLASS B - (Ø quarter/year)

Norm	EN ISO 1307:2008, ISO 13363:04 type 2 class B, Lloyd's register nr. 96/00127 (E4), RINA nr. DIP061008CS 20/03/08, SAE J 2006:03	Construction tube	Smooth, exhaust and sea water resistant rubber
Working pressure	3 bar	Color tube	Black
Vacuum	0,80 bar	Cover	Fabric finish, Corrugated
Min. temperature	-30 °C	Color cover	Black
Max. temperature	+100 °C	Reinforcements	Steel spiral, Textile plies

Art.-no.	Ø Inner (mm)	Ø Outer (mm)	Bending radius (mm)	Weight (kg/mtr)	Length (mtr)
3737040000	40,0	50,0	80	0,900	20
3737045000	45,0	57,0	90	1,000	20
3737050000	51,0	63,0	100	1,100	20
3737060000	60,0	71,0	120	1,500	20
3737075000	76,0	90,5	150	2,100	20
3737090000	90,0	104,0	180	2,650	20
3737100000	102,0	119,0	200	3,050	20
3737125000	127,0	143,0	250	3,600	20

**Application:** Very flexible wet exhaust hose. Also suitable for the cooling of heat exchangers on motor yachts up to 24 meters.

**Remark:**

- Cutted length possible

