

## EUROLON®

### Layflat PVC water hose



Norm	EN ISO 1307:2008	Color tube	Blue
Min. temperature	-20 °C	Compound cover	PVC
Max. temperature	+60 °C	Color cover	Blue
Compound tube	PVC		

Art.-no.	Ø Inner (mm)	Wall (mm)	Ø Outer (mm)	Measured flat (mm)	WP at 20°C (bar)	Weight (kg/mtr)	Length (mtr)
4010025000	25,0	2,0	29,0	39	7,0	0,180	50
4010032000	32,0	2,0	36,0	50	7,0	0,210	100
4010038000	38,0	2,0	42,0	60	7,0	0,240	100
4010050000	51,0	2,0	55,0	82	7,0	0,350	100
4010063000	63,0	2,0	67,0	99	7,0	0,450	100
4010075000	76,0	2,0	80,0	118	6,0	0,610	100
4010100000	102,0	2,0	106,0	160	6,0	0,920	100
4010125000	127,0	2,0	131,0	196	6,0	1,150	50
4010150000	152,0	2,0	156,0	239	6,0	1,570	50
4010200000	203,0	2,0	207,0	319	4,0	2,150	50

**Application:** High-quality flat collapsible water supply and discharge hose, can be used as a sprinkler hose in agriculture and gardening. Also suitable for water treatment on construction sites and in industry. Hose is unique because of its advanced production method (one-way extrusion) in which the inserts are incorporated into the material during the extrusion process. The hose consists of one piece and is therefore less vulnerable to mechanical damage and leakage is reduced to a minimum. The hose differs qualitatively from various other products available on the market.

**Remark:**

- Cutted length possible

**We recommend assembly with**

5110  
Storz couplings



6060  
ABA clamps

