


POLYFORM



Food quality water hose
limited chemical resistant.

Marking:  Polyform - Reg. EU 10/2011 - Dimension

Norm	EN ISO 1307:2008, EU 10/2011 Cat. A, EU 10/2011 Cat. B, EU 10/2011 Cat. C, EU 1935/2004, LFGB	Construction tube	Smooth
Material	PVC	Cover	Smooth
Min. temperature	-20 °C	Colour	Transparent
Max. temperature	+60 °C		

Art.-no.	Ø Inner (mm)	Wall (mm)	Ø Outer (mm)	Weight (kg/mtr)	Length (mtr)
4041003005	3,0	1,0	5,0	0,016	100
4041004006	4,0	1,0	6,0	0,020	100
4041004007	4,0	1,5	7,0	0,032	100
4041005008	5,0	1,5	8,0	0,040	100
4041006009	6,0	1,5	9,0	0,045	100
4041006010	6,0	2,0	10,0	0,060	100
4041007010	7,0	1,5	10,0	0,051	100
4041008012	8,0	2,0	12,0	0,080	50
4041009013	9,0	2,0	13,0	0,088	50
4041010014	10,0	2,0	14,0	0,096	50
4041012016	12,0	2,0	16,0	0,112	50
4041013018	13,0	2,5	18,0	0,155	50
4041014019	14,0	2,5	19,0	0,165	50
4041015020	15,0	2,5	20,0	0,175	50
4041016022	16,0	3,0	22,0	0,230	50
4041018024	18,0	3,0	24,0	0,250	50
4041019027	19,0	4,0	27,0	0,370	50
4041020026	20,0	3,0	26,0	0,280	50
4041022028	22,0	3,0	28,0	0,300	50
4041025031	25,0	3,0	31,0	0,340	50
4041030037	30,0	3,5	37,0	0,470	50
4041032040	32,0	4,0	40,0	0,580	50
4041038048	38,0	5,0	48,0	0,860	50
4041050060	50,0	5,0	60,0	1,100	50

Application: Transparent, smooth PVC hose without insertions. Crystal clear by using first choice PVC granulate. The hose can be used for various applications in the food and pharma industry. Can also be used for various industrial applications and as a cable protection hose.

Remark:

- Cutted length not possible

