

## COSMO®



Thermoplastic suction hose

Marking: Cosmo® - Dimension

Norm	EN ISO 1307:2008	Color tube	Green transparent
Vacuum	0,60 bar	Compound cover	PVC
Min. temperature	-15 °C	Cover	Slightly corrugated
Max. temperature	+60 °C	Color cover	Green transparent
Compound tube	PVC	Reinforcements	Rigid PVC spiral
Construction tube	Smooth	Color spiral	White

Art.-no.	Ø Inner (mm)	Ø Outer (mm)	Bending radius (mm)	Weight (kg/mtr)	Length (mtr)
4400020000	20,0	26,0	80	0,230	50
4400025000	25,0	31,0	100	0,280	50
4400032000	32,0	39,0	128	0,380	50
4400038000	38,0	45,0	152	0,480	50
4400050000	51,0	59,0	204	0,750	50
4400060000	60,0	69,0	240	0,970	50
4400063000	63,0	72,0	252	1,000	50
4400075000	76,0	86,0	304	1,350	50
4400090000	90,0	102,0	360	1,800	50
4400100000	102,0	114,0	408	2,200	50

**Application:** Flexible, translucent, lightweight hose for suction of water under light working conditions for both industrial and agricultural applications. The Cosmo can also be used as a pond hose in combination with light vacuum pumps. In addition, the hose is also frequently used on construction sites for water treatment.

**Remark:**

- Cutted length possible
- We recommend using cord for hose assembly

**We recommend assembly with**

5510  
Kamlok couplings



5124  
Storz couplings



6200  
Super clamps

