







DHV 30 HV TANK - HIGH VACUUM



STEELWORKS AND FOUNDRIES





POWER PLANTS



HEAVY INDUSTRY





- ✓ Sturdy vacuum cleaner for intensive use
- ✓ Powerful lobe pump with electric motor
- ✓ High performances and long-lasting
- ✓ High efficiency filtration
- ✓ Semi-automatic filter cleaning system

- ✓ Easy to handle
- ✓ Detachable container with fork lift intakes which make it is easy to handle
- ✓ Discharge system by means of a valve
- ✓ Low noise level
- ✓ Great autonomy of the system

| SUCTION UNIT | | |
|-----------------------|--------|----------|
| Voltage | V - Hz | 400 - 50 |
| Power | kW | 30 |
| Electrical protection | IP | 55 |
| Max waterlift | mmH2O | 8500 |
| Max air flow | m³/h | 1300 |
| Suction inlet | mm | 140 |

| | FILTER UNIT | | |
|---|-----------------------|----------------|------------------|
| · | Filter Type | | 30 Sleeves |
| | Surface - Diameter | cm²-mm | 160.000 - 120 |
| | Material - Efficiency | IEC 60335-2-69 | Polyester - M |
| | Cleaning system | | Automatic |
| | Secondary filter | | Safety cartridge |
| | Surface | cm² | 70.000 |
| | | | |

| COLLECTION UNIT | | |
|-----------------|-----|--------------------|
| Capacity | lt. | 800 |
| Discharge type | | Forkable container |
| | | |
| VOLUME | | |
| Dimensions | cm | 168x160x291h |
| Weight | kg | 2340 |





SUCTION UNIT

The suction unit is provided with a volumetric vacuum pump with tri-lobe rotors which can reach very high airflow and waterlift levels

A safety filter guarantees the maximum protection for both motor and pump

The electrical panel is suitable for remote control and a push-button is installed on the chassis as standard



FILTER UNIT

2 sets of filtering sleeves work continuously and alternatively. Doing so, they guarantee the maximum filtration efficiency and protection for the motor

The filter is cleaned by an automatic system with backwash of the chambers. Compressed air is provided by an onboard compressor.



COLLECTION UNIT

Forklift intakes for easy discharge.

The material is collected into a capacious and detachable container, which is easy to handle thanks to fork lift intakes

The material is safely and quickly discharged by means of a lever

The unit is manufactured with thick painted steel for improved sturdiness and long-lasting lifetime



OPTIONALS

- ✓ ABSOLUTE HEPA FILTER
- ✓ ATEX CERTIFICATION
- ✓ ALTERNATIVE DISCHARGE SYSTEMS