



ADWP/ADWS



Manual sliding damper with gaskets for a better air tightness. Identical construction as the automatic models, but without accessories. Galvanised steel or stainless steel AISI 304. Thickness: 0,9 - 2,0 mm.



Measures on the next page

ADWP/ADWS

Ø mm	A mm	B mm	C mm	D mm	Blade th. mm	House th. mm
50*	293	192,5	145	139,5	2	1,5
63*	293	192,5	145	139,5	2	1,5
76*	338	222,5	145	156,5	2	1,5
80	338	222,5	125	156,5	2	1,5
100	398	263	125	176,5	2	1,5
102*	398	263	125	176,5	2	1,5
108*	475	313,5	145	201,5	2	1,5
120	475	313,5	125	201,5	2	1,5
125	475	313,5	125	201,5	2	1,5
127*	475	313,5	145	201,5	2	1,5
140	548	363	125	226,5	2	1,5
150	548	363	125	226,5	2	1,5
152*	548	363	125	226,5	2	1,5
160	574	382,5	125	236,5	2	1,5
180	699	463	125	276,5	2	1,5
200	699	463	125	276,5	2	1,5
202*	699	463	125	276,5	2	1,5
225	847	562	165	347	3	2,0
250	849	562	165	371	3	2,0
300	1050	692	165	422	3	2,0
315	1050	692	165	422	3	2,0
350	1160	763	165	472	3	2,0
400	1310	863	165	522	3	2,0
450	1192	980	250	623	4	3,0
500	1644	1082	250	673	4	3,0
550	1829	1207	250	713	4	3,0
600	1964	1292	250	783	4	3,0
630	2044	1342	250	813	4	3,0
650	2044	1342	250	813	4	3,0
700	2324	1542	250	893	4	3,0
800	2564	1692	260	973	4	3,0

*With straight edge. The rest is with pull ring edge.