



KITT - Installation sealant

Installation accessories

Sealant for ducts and pipe passages.

KITT-01/B75 Butyl: Especially suitable in cold or wet environments as water-based products are not useful. Clean with lacquer naphtha or the like after application. Product characteristics: Frost resistant; Resistant to water, weak acids and alkalis; Non-sticky after about 12 hours; Aromate; Application temperature -25°C to +40°C; Operating temperature from -25°C till +70°C

KITT-02/Allround Silicone: A neutral high elastic silicone sealant for sealing inside and outside. Brackets on e.g. metals, glass, ceramics and PVC. Product characteristics: Tamper; UV-resistant; Treated Anti-mold; Free of vinegar; Skin formation after about 5 minutes; Product meets CE standard; Application temperature from +1°C to +30°C; Operating temperature from -60°C till +120°C

KITT-03/Seal & Resist: an oil resistant and nitrile rubber based sealant. The product is suitable as a seal in slightly harsher environments, such as paint booths and kitchen ducts. Clean with lacquer naphtha or the like after application. Product Features: Water resistant, weak acids, alkalis, grease and oils; Non-sticky after about 30 minutes; Application temperature from -25°C to +40°C; Operating temperature from -25°C till +100°C



KITT - Installation sealings



KITT-04 - Dispensing gun

Art.no	Weight (kg)
KITT-01	0,35
KITT-02	0,35
KITT-03	0,35
KITT-04	0,25