



Sweeper hose, heavy and reinforced, interior folds

Application

- municipal vehicle: sweeper, sweeping machine

Properties

- heavy duty and reinforced
- highly abrasion resistant
- microbe resistant
- very good low temperature flexibility
- REACH according to --> Technology / Technical Information / REACH

- conforms to RoHS guideline

Temperature Range

- -40 °C to 90 °C

Design

- AIRDUC® profile hose
- spring steel wire firmly embedded in wall
- wall: special premium polyurethane (Pre-PUR®)
- wall thickness 1,5 to 1,8 mm approx.

- wall thickness 1,5 to 1,8 mm approx.

- reinforcement of the primary abrasion areas

Delivery variants

- further diameters and lengths available on request
- transparent (standard)
- special colours: transparent, partially coloured, completely coloured
- customer-specific branding

I.D.	outer Ø	Pressure	Vacuum	Bending Radius	Weight	Dimensions in Stock	Order No.
(in / mm)	(mm)	(bar)	(bar)	(mm)	(kg/m)	(m)	
8 / 200-203	215.00	0,365	0,125	178.00	2.65	5	355-0203-5015
- / 208	220.00	0,360	0,120	182.00	2.74	5	355-0208-5015
10 / 254	266.00	0,295	0,075	219.00	3.56	5	355-0254-5016
12 / 305	320.00	0,255	0,060	262.00	5.10	5	355-0305-5015

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/

Accessories



CONNECT 270-271



CONNECT 240 + 241 AS



CLAMP 211

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/