

CLAMP 212



Bridge clamp for attaching externally corrugated spiral hoses

Properties

- practically leak-proof and secure clamping with special bridge geometry
- easily and quickly fitted
- re-usable

- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Design

- Quality: W2; clamp strip: stainless steel 1.4301 = AISI 304; screw: galvanised steel; Body: stainless steel 1.4016 = AISI 430; bridge: stainless steel 1.4301 = AISI 304 (INOX)

- Quality: W2; clamp strip: stainless steel 1.4301 = AISI 304; screw: galvanised steel; Body: stainless steel 1.4016 = AISI 430; bridge: stainless steel 1.4301 = AISI 304 (INOX)

Delivery variants

- further diameters available on request

Suitable for Hose I.D.	Clamping Range	Band Width	Order No.
(mm)	(mm)	(mm)	
AIRDUC® & PROTAPÉ® 44 mm			
13-16	9-19	5	212-0009-0000
15-18	13-20	5	212-0013-0000
18-26	17-29	5	212-0017-0000
22-28	20-28	5	212-0020-0000
25-29	22-37	9	212-0022-0000
30-35	27-47	9	212-0027-0000
32-37	29-47	9	212-0029-0000
38-44	35-55	9	212-0035-0000
AIRDUC® & PROTAPÉ® 45 mm, CP & PROTAPÉ® TPE 326 MEMORY 70 mm			
45-50	40-60	9	212-0040-0000
50-55	45-65	9	212-0045-0000
60-65	55-75	9	212-0055-0000
70-75	65-85	9	212-0065-0000
80-85	75-95	9	212-0075-0000
90-95	85-105	9	212-0085-0000
100-105	95-115	9	212-0095-0000
110-115	105-125	9	212-0105-0000
120-125	115-135	9	212-0115-0000
130-135	125-145	9	212-0125-0000
140-145	135-155	9	212-0135-0000
150-155	145-165	9	212-0145-0000
160-165	155-175	9	212-0155-0000
170-175	165-185	9	212-0165-0000
180-185	175-195	9	212-0175-0000
190-195	185-205	9	212-0185-0000
200-205	195-215	9	212-0195-0000
210-215	205-225	12	212-0205-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/

CLAMP 212

Suitable for Hose I.D.	Clamping Range	Band Width	Order No.
(mm)	(mm)	(mm)	
220-225	215-235	12	212-0215-0000
230-235	225-245	12	212-0225-0000
240-245	235-255	12	212-0235-0000
250-255	245-265	12	212-0245-0000
260-265	255-275	12	212-0255-0000
270-275	265-285	12	212-0265-0000
280-285	275-295	12	212-0275-0000
285-290	280-300	12	212-0280-0000
290-295	285-305	12	212-0285-0000
300-305	295-315	12	212-0295-0000
310-315	305-325	12	212-0305-0000
320-325	315-335	12	212-0315-0000
330-335	325-345	12	212-0325-0000
340-345	335-355	12	212-0335-0000
350-355	345-365	12	212-0345-0000
360-365	355-375	12	212-0355-0000
370-375	365-385	12	212-0365-0000
380-385	375-395	12	212-0375-0000
390-395	385-405	12	212-0385-0000
400-405	395-415	12	212-0395-0000
410-415	405-425	12	212-0405-0000
430-435	425-445	12	212-0425-0000
450-455	445-465	12	212-0445-0000
470-475	465-485	12	212-0465-0000
485-490	480-500	12	212-0495-0000
500-505	495-515	12	212-0480-0000
510-535	505-545	12	212-0505-0000
520-545	515-555	12	212-0515-0000
550-575	545-585	12	212-0545-0000
580-605	575-615	12	212-0575-0000
600-625	595-635	12	212-0595-0000
630-655	625-665	12	212-0625-0000
650-675	645-685	12	212-0645-0000
675-700	670-710	12	212-0670-0000
700-725	695-735	12	212-0695-0000
730-755	725-765	12	212-0725-0000
750-775	745-785	12	212-0745-0000
800-825	795-835	12	212-0795-0000
825-850	820-860	12	212-0820-0000
850-875	845-885	12	212-0845-0000
880-905	875-915	12	212-0875-0000
900-925	895-935	12	212-0895-0000
925-950	920-960	12	212-0920-0000
950-975	945-985	12	212-0945-0000
975-1000	970-1010	12	212-0970-0000
990-1015	985-1025	12	212-0985-0000
1050-1075	1045-1085	12	212-1045-0000
1080-1125	1075-1135	12	212-1075-0000
CP Ø 38-65 mm, PROTAPÉ® TPE 326 MEMORY Ø 51-65mm			
38-45	35-55	9	212-0035-2002
45-50	40-60	9	212-0040-2002
50-55	45-65	9	212-0045-2002


Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/

CLAMP 212

Suitable for Hose I.D.	Clamping Range	Band Width	Order No.
(mm) 60-65	(mm) 55-75	(mm) 9	212-0055-2002

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/

Accessories



CONNECT 228



CONNECT 270-271

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/