



Threaded adapter

### Application

- food industry, pharmaceutical industry: foodstuff, pharmaceutical
- vacuum conveying equipment, vacuum hopper, suction conveyor, dosing system
- pelleting machines/ tablet presses

### Properties

- thread reference DIN ISO 228
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

### Temperature Range

- -40°C to 90°C

- -40°C to 90°C

### Delivery variants

- further diameters available on request
- gas and liquid tight as pre-fitted version

Size (mm)	Weight (kg/pcs)	Suitable for Hose I.D. (mm)	Order No.
<b>Thread adapter DIN ISO 228; Edelstahl 1.4404 (gestempelt) = AISI 316L; (please select the hose and the assembly separately)</b>			
25	0,360	ø 25	234-0025-2920
32	0,450	ø 32	234-0032-2920
38	0,520	ø 38	234-0038-2920
40	0,610	ø 40	234-0040-2920
50	0,850	ø 50	234-0050-2920
65	0,896	ø 65	234-0065-2920
75	1,000	Ø 75	234-0075-2920
80	1,400	ø 80	234-0080-2920
100	2,030	ø 100	234-0100-2920
<b>Thread adapter DIN ISO 228; aluminium; (please select the hose and the assembly separately)</b>			
25	0,120	ø 25	234-0025-2917
32	0,160	ø 32	234-0032-2917
38	0,180	ø 38	234-0038-2917
40	0,210	ø 40	234-0040-2917
50	0,290	ø 50	234-0050-2917
65	0,310	ø 65	234-0065-2917
75	0,400	Ø 75	234-0075-2917
80	0,480	ø 80	234-0080-2917
100	0,700	ø 100	234-0100-2917
<b>Thread adapter DIN ISO 228; electro-galvanised steel; (please select the hose and the assembly separately)</b>			
25	0,360	ø 25	234-0025-2918
32	0,450	ø 32	234-0032-2918
38	0,520	ø 38	234-0038-2918
40	0,610	ø 40	234-0040-2918
50	0,850	ø 50	234-0050-2918
65	0,896	ø 65	234-0065-2918
75	1,000	Ø 75	234-0075-2918

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/)

# CONNECT THREAD FITTING 234



Size	Weight	Suitable for Hose I.D.	Order No.
(mm)	(kg/pcs)	(mm)	
80	1,400	ø 80	234-0080-2918
100	2,030	ø 100	234-0100-2918

Thread adapter DIN ISO 228; stainless steel 1.4301 (stamped) = AISI 304; (please select the hose and the assembly separately)			
25	0,360	ø 25	234-0025-2919
32	0,450	ø 32	234-0032-2919
38	0,520	ø 38	234-0038-2919
40	0,610	ø 40	234-0040-2919
50	0,850	ø 50	234-0050-2919
65	0,896	ø 65	234-0065-2919
75	1,000	Ø 75	234-0075-2919
80	1,400	ø 80	234-0080-2919
100	2,030	ø 100	234-0100-2919

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/)

## Accessories



CONNECT SAFETY CLAMP ASSEMBLY 231



CONNECT PRESS ASSEMBLY 232



CONNECT MOULD ASSEMBLY 233

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/)