



Soft sleeve to slide onto connectors or push into pipes

Application

- industrial vacuum cleaners, vacuum cleaners
- municipal vehicle: sweeper, sweeping machine
- municipal vehicle: lawn mower, slope mower, leaf blower/ leaf collector
- scrubber, floor cleaning machine

Properties

- easily and quickly fitted
- re-usable (threaded version)
- gas and liquid tight as pre-fitted version

- highly abrasion resistant
- microbe and hydrolysis resistant
- good resistance to oil, gasoline and chemicals
- version 241 - permanently antistatic wall: electrical and surface resistance approx. $10^9 \Omega$
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40°C to 90°C
- short time to 125°C

- short time to 125°C

Design

- wall: special premium ester-polyurethane (Pre-PUR®)

Delivery variants

- further diameters available on request
- black (standard)
- special colours: full coloured
- gas and liquid tight as pre-fitted version

Rec. Adapter Ø (mm)	Rec. Adapter length (mm)	Threading depth Hose (mm)	Total Length (mm)	Weight (kg/pcs)	Suitable for Hose I.D. (mm)	Order No.
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345						
38	44	40	85	0,085	38	240-0038-0000
40	44	40	85	0,084	40	240-0040-0000
50	49	41	90	0,089	50	240-0050-0000
60	49	41	90	0,120	60	240-0060-0000
70	52	44	100	0,146	70	240-0070-0000
32	44	40	85	0,070	32	241-0032-8500
75	60	47	107	0,200	75	241-0075-8500
80	60	52	112	0,250	80	241-0080-8500
100	65	57	122	0,310	100	241-0100-8500
125	75	62	137	0,480	125	241-0125-8500
150	85	70	155	0,680	150	241-0150-8500
200	100	80	180	1,100	200	241-0200-8500
250	105	90	195	1,500	250	241-0250-8500
300	115	100	215	2,260	300	241-0300-8500
Threaded; Suitable for Hose 356						
38	44	40	85	0,070	38	241-0038-8501
40	44	40	85	0,080	40	241-0040-8501
50	49	41	90	0,080	50	241-0050-8501
60	49	41	90	0,120	60	241-0060-8501
70	52	44	100	0,150	70	241-0070-8501
75	60	47	107	0,200	75	241-0075-8501
80	60	52	112	0,250	80	241-0080-8501
100	65	57	122	0,310	100	241-0100-8501
125	75	62	137	0,480	125	241-0125-8501
150	85	70	155	0,680	150	241-0150-8501

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/

CONNECT 240 + 241 AS



Rec. Adapter Ø	Rec. Adapter length	Threading depth Hose	Total Length	Weight	Suitable for Hose I.D.	Order No.
(mm)	(mm)	(mm)	(mm)	(kg/pcs)	(mm)	
200	100	80	180	1,100	200	241-0200-8501
250	105	90	195	1,500	250	241-0250-8501
300	115	100	215	2,260	300	241-0300-8501

pre-fitted						
38	44	40	85	0,070	38	241-0038-8551
40	44	40	85	0,080	40	241-0040-8551
50	49	41	90	0,080	50	241-0050-8551
60	49	41	90	0,120	60	241-0060-8551
70	52	44	100	0,150	70	241-0070-8551
75	60	47	107	0,200	75	241-0075-8551
80	60	52	112	0,250	80	241-0080-8551
100	65	57	122	0,310	100	241-0100-8551
125	75	62	137	0,480	125	241-0125-8551
150	85	70	155	0,680	150	241-0150-8551
200	100	80	180	1,100	200	241-0200-8551
250	105	90	195	1,500	250	241-0250-8551
300	115	100	215	2,260	300	241-0300-8551

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/