



Soft sleeve to slide onto connectors or push into pipes, electrically conductive

Application

- industrial vacuum cleaners, vacuum cleaners

Properties

- easily and quickly fitted
- re-usable (threaded version)
- highly abrasion resistant
- microbe and hydrolysis resistant

- good resistance to oil, gasoline and chemicals
- electrically conductive wall: electrical and surface resistance $<10^3\Omega$ (according to NFPA 652 $<10^6\Omega$)
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40 °C to 90 °C
- short time to 125 °C

Design

- Wall of EC version electrically conductive $<10^3$: electrically conductive Premium Ester-Polyurethane (Pre-PUR®)

Delivery variants

- further diameters available on request
- black (standard)
- special colours: full coloured

| Rec. Adapter Ø | Rec. Adapter length | Threading depth Hose | Total Length | Weight | Suitable for Hose I.D. | Order No. |
|---|---------------------|----------------------|--------------|----------|------------------------|---------------|
| (mm) | (mm) | (mm) | (mm) | (kg/pcs) | (mm) | |
| Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345 | | | | | | |
| 38 | 44 | 40 | 85 | 0,094 | 38 | 240-0038-1003 |
| 40 | 44 | 40 | 85 | 0,087 | 40 | 240-0040-1003 |
| 50 | 49 | 41 | 90 | 0,103 | 50 | 240-0050-1003 |
| 60 | 49 | 41 | 90 | 0,133 | 60 | 240-0060-1003 |
| 70 | 52 | 44 | 96 | 0,163 | 70 | 240-0070-1003 |

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/