



TRI clamp adapters based on DIN 32676 and ISO 2853

Application

- food industry, pharmaceutical industry: foodstuff, pharmaceutical
- pelleting machines/ tablet presses
- vacuum conveying equipment, vacuum hopper, suction conveyor, dosing system

Properties

- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40 °C to 90 °C

Design

- fitting: stainless steel 1.4404 (stamped) = AISI 316L
- matching accessories: seal (silicone white, FDA), adapter (stainless steel 1.4404, stamped), clamp (stainless steel)

Delivery variants

- further diameters available on request
- gas and liquid tight as pre-fitted version

Size (mm)	Nominal width tube (inch)	Outer-Ø flange (mm)	Weight (kg/pcs)	Suitable for Hose I.D. (mm)	Order No.
--------------	------------------------------	------------------------	--------------------	--------------------------------	-----------

Adapter TRI-CLAMP DIN 32676; Edelstahl 1.4404 (gestempelt) = AISI 316L; (please select the hose and the assembly separately)

25	-	50,5	0,090	ø 25	245-0025-2914
32	-	50,5	0,090	ø 32	245-0032-2914
40	-	50,5	0,080	ø 40	245-0040-2914
50	-	64,0	0,160	ø 50	245-0050-2914
65	-	91,0	0,180	ø 65	245-0065-2914
80	-	106,0	0,380	ø 80	245-0080-2914
100	-	119,0	0,420	ø 100	245-0100-2914
150	-	183	1,200	Ø 150	245-0150-2914

Adapter TRI-CLAMP ISO 2852; Edelstahl 1.4404 (gestempelt) = AISI 316L; (please select the hose and the assembly separately)

-	1"	50,5	0,09	ø 25	245-0025-2923
-	1 1/2"	50,5	0,11	ø 40	245-0040-2923
-	2"	64,0	0,16	ø 50	245-0050-2923
-	2 1/2"	77,5	0,17	ø 65	245-0065-2923
-	3"	91,0	0,35	Ø 75	245-0075-2923
-	4"	119,0	0,42	ø 100	245-0100-2923

Matching accessories; Adapter for welding on DIN 32676

25	-	50,5	-	ø 25	245-0025-8913
32	-	50,5	-	ø 32	245-0032-8913
40	-	50,5	-	ø 40	245-0040-8913
50	-	64,0	-	ø 50	245-0050-8913
65	-	91,0	-	ø 65	245-0065-8913
80	-	106,0	-	ø 80	245-0080-8913
100	-	119,0	-	ø 100	245-0100-8913

Matching accessories; Adapter for welding on ISO 2852

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/

CONNECT TRI-CLAMP FITTING 245



Size (mm)	Nominal width tube (inch)	Outer-Ø flange (mm)	Weight (kg/pcs)	Suitable for Hose I.D. (mm)	Order No.
-	1"	50,5	-	ø 25	245-0025-8917
-	1 1/2"	50,5	-	ø 40	245-0040-8917
-	2"	64,0	-	ø 50	245-0050-8917
-	2 1/2"	77,5	-	ø 65	245-0065-8917
-	3"	91,0	-	Ø 75	245-0075-8917
-	4"	119,0	-	ø 100	245-0100-8917

Matching accessories; Clamp; stainless steel

-	-	50,5	-	-	245-0025-8914
-	-	64,0	-	-	245-0050-8914
-	-	77,5	-	-	245-0055-8914
-	-	91,0	-	-	245-0065-8914
-	-	106,0	-	-	245-0080-8914
-	-	119,0	-	-	245-0100-8914

Matching accessories; seal DIN 32676; Silicone, white

25	-	50,5	-	ø 25	245-0025-8912
32	-	50,5	-	ø 32	245-0032-8912
40	-	50,5	-	ø 40	245-0040-8912
50	-	64,0	-	ø 50	245-0050-8912
65	-	91,0	-	ø 65	245-0065-8912
80	-	106,0	-	ø 80	245-0080-8912
100	-	119,0	-	ø 100	245-0100-8912

Matching accessories; seal ISO 2852; Silicone, white

-	1"	50,5	-	ø 25	245-0025-8916
-	1 1/2"	50,5	-	ø 40	245-0040-8916
-	2"	64,0	-	ø 50	245-0050-8916
-	2 1/2"	77,5	-	ø 65	245-0065-8916
-	3"	91,0	-	Ø 75	245-0075-8916
-	4"	119,0	-	ø 100	245-0100-8916

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/

Accessories



CONNECT SAFETY CLAMP ASSEMBLY
231



CONNECT PRESS ASSEMBLY 232



CONNECT MOULD ASSEMBLY 233

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/