

### European Headquarters

**Tiger-Vac Europa S.R.L.**  
Via Marie Curie 17  
Zona Industriale Ponte Rizzoli  
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)  
Fax: ((39) 051 4695077)  
Website: <http://www.tiger-vac.eu>  
Email: [info@tiger-vac.it](mailto:info@tiger-vac.it)

### International Headquarters

**Tiger-Vac International Inc.**  
2020 Dagenais Blvd. Ouest  
Laval, Quebec  
Canada H7L 5W2

Tel: (450-625-0099)  
Fax: (450-625-3388)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)



**ATEX** CE EX II 3 D  
Ex h tc IIIC T200°C (T85°C for BLSLSD version) Dc IP6X

LCIE 19 ATEX 1001 X




**IECEx 3rd Party Certified**  
Ex h tc IIIC T200°C (T85°C for BLSLSD version) Dc IP6X  
**IECEx LCIE 15.0048**



This model can be used to Recover Combustible Dusts such as Dust Groups :  
**IIIA** Combustible Flyings (lints of cotton, wood chips, etc.)  
**IIIB** Non-Conductive Dusts (flour dust, grain dust, flour, sugar, starch, wood, plastic, carbonaceous dusts, coal, carbon black)  
**IIIC** Conductive Dusts (combustible metal dust, aluminum, magnesium, commercial alloys)

**ESD Safe** Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.  
We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)



3D Printing



EX Certified



Static Dissipating



HEPA - Included



High Filtration Efficiency Unit



Stainless General



SD Tools & Accessories



Dry Recovery



High Efficiency Cyclone



Brushless Motor Available

## Specifications for C-10 EX DT (PRS-HEC)

Name	Part Number	Voltage	Hertz	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Plug Type
C-10 EX DT (PRS-HEC)	113230B	220-240 V	50/60 Hz	Single	1200 W	1.2 kW	5 A	194 m <sup>3</sup> /h	2504 mm H <sub>2</sub> O	Not Included
	Sound Level: 72 dB(A)									

Please note that specifications are subject to change without notice

## Technical Sheet for C-10 EX DT (PRS-HEC)

RECOVERY TANK - Optional	
Part #	Description
223001-ASM1	RECOVERY TANK ASSEMBLY FOR HEC-25L SS304 w/CONDUCTIVE WHEELS INCLUDES CLOSING LID w/HANDLE