

European Headquarters

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)
Website: <http://www.tiger-vac.eu>
Email: info@tiger-vac.it

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com



ATEX®
CE EX II 3D
Ex h tc IIIC T200°C (T85°C for BLSD version)
Dc IP6X

LCIE 19 ATEX 1001 X

IECEx 3rd Party Certified



Ex h tc IIIC T200°C (T85°C for BLSD version)
Dc IP6X
IECEx LCIE 15.0048



Static
Dissipating



HEPA -
Included



High Filtration
Efficiency Unit



Stainless
Steel
General



SD Accessories
- Included



Dry
Recovery



Detachable
Tank



Brushless
Motor Available

This model can be used to Recover
Combustible Dusts such as Dust Groups :
IIIA Combustible Flyings (lints of cotton, wood
chips, etc.)
IIIB Non-Conductive Dusts (flour dust, grain
dust, flour, sugar, starch, wood, plastic,
carbonaceous dusts, coal, carbon black)
IIIC Conductive Dusts (combustible metal
dust, aluminum, magnesium, commercial
alloys)



ESD Safe Vacuum Systems for Hazardous
Locations are designed to prevent ignition
hazards.
We use metal parts or Static Dissipative
Powder Coating to prevent Electrostatic
Discharge (ESD)

Specifications for C-35L EX DT (MRP)

Name	Part Number	Voltage	Hertz	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Plug Type	Dry Recovery - Tank
C-35L EX DT (MRP)	111784B	220-240 V	50/60 Hz	Single	1200 W	1.2 kW	5 A	194 m ³ /h	2504 mm H ₂ O	Not Included	35 L
	Dimensions: H119 cm x W66 cm x L66 cm Weight: 42 kg. Sound Level: 72 dB(A)										
C-35L EX DT (MRP) BLSD	111784B-BLSD	220-240 V	50/60 Hz	Single	1100 W	1.1 kW	8 A	215 m ³ /h	2250 mm H ₂ O	Not Included	35 L
	Dimensions: H119 cm x W66 cm x L66 cm Weight: 42 kg. Sound Level: 72 dB(A)										
Description: With Brushless Motor											

Please note that specifications are subject to change without notice

Technical Sheet for C-35L EX DT (MRP)

HEPA FILTERS - Included	
Part #	Description
212304B-HD	HEPA FILTER, 99.99% EFFICIENCY ON 0.3 MICRON, HEAVY DUTY CONSTRUCTION
215372	HEPA FILTER WITH GASKETS ON BOTH SIDES, 99.99% ON 0.3 MICRON, 11.522" OD x 9.066" ID x 2" HIGH
211854	HEPA FILTER (H14) WITH GASKET, 2"(50mm) HIGH

FILTERS AND ACCESSORIES - Included

Part #	Description
214182A	FILTER CARTRIDGE, ALUMINIZED SPUN BOND POLYESTER, 16"H x 3.63"ID x 7.932"OD, 1" PLEATS, 13 SQ.FT
212244A	SD* MICRO SAFETY FILTER (EPITROPIC POLYESTER w/PTFE) ASSEMBLY WITH CLAMP

POLY LINER RECOVERY BAGS AND ACCESSORIES - Optional

Part #	Description
212100CS	CONDUCTIVE POLY LINER WITH DRAW STRING (35/38 LITRES)
213780	POLY LINER RETAINER PLATE ASSEMBLY (FOR USE WITH MOTORS UP TO 5HP)

TOOLS AND ACCESSORIES - Included

Part #	Description
383440B	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASMBLY(NO WIRE) 1.5"(38mm) x 10'(3m) FOR 2" CAMLOCK INTAKE
381163	DOUBLE BEND WAND ASSEMBLY (2pc), 1.5" (38mm) x 54" (137cm), CHROME w/ALUMINUM TOOL COUPLING
381377A	FLOOR TOOL ALUMINUM 1.5"(38mm) x 14"(36cm) WITH CONDUCTIVE BRISTLES
381188	CREVICE TOOL SD*, 1.5" (38mm) x 11" (28cm), ALUMINUM