

ATEX

ATEX 1st Party Certified
CE II 3D
Ex tc IIIB T200°C Dc IP6X



Groups F and G Cleanroom Compatible Dust (Combustible and Toxic/Nuisance)
IIIB Cleanroom Compatible Dust (Combustible and Toxic/Nuisance)

ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.
We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)



Characteristics



ULPA - Included



High Filtration Efficiency Unit



Static Dissipating



Stainless General



SD Accessories - Included



Dry Recovery

- Long lasting brushless motor rated for continuous duty
- For housekeeping and general cleaning
- EMI/RFI shielded and ESD safe
- 5-stage filtration system, includes dual ULPA filters (U15) (one for the working air and one for the cooling air), double cloth filter, and disposable filter bags
- Includes an indicator light to warn of vacuum blockage
- Designed to be autoclavable - stainless steel SAE 316 electropolished (except motor housing)

Specifications

CWR-10 EX (4W) BLSD	110540B-BLSD
Model Name	CWR-10 EX (4W) BLSD
Type (Powerhead)	Electric
Voltage	220-240 V
Hertz	50/60 Hz
Phase	Single
Wattage	1100 W
Power	1.1 kW
Amperage	8 A
Air Flow	215 m ³ /h
Vacuum Pressure	2250 mm H ₂ O
Sound Level	75 dB(A)
Plug Type	Not Included
Suction Inlet	38 mm
Cart Type	4 Wheel Dolly (4W)
Filter Cleaning	None
Dry Recovery - Disposable Filter Bag	19 L
Length	76 cm
Width	46 cm
Height	64 cm
Weight (Vacuum Only)	30 kg.
Cord Length	10.6 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Conductive Recovery Bags - included



CWR EX Tools and Accessories - Included