

Characteristics

ATEX 3rd Party Certified Ex d IIA T3 Gb Ex t IIIC T200°C Db IP6X

LCIE 03 ATEX 6297



ATEX

GUARANTEED for the Safe Recovery of Combustible/Conductive Dusts

ESD Safe Vacuum Cleaners for Hazardous Locations are designed to prevent ignition hazards. We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)





Less than 10

ohms



HEPA

HEPA -

Included



ULPA - Optional



Dry Recovery

304

High Filtration Efficiency Unit

Tank

Compatible Applications

- Legally certified explosion proof/dust ignition proof
- Less than 10 ohms of resistivity
- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- Cleanroom compatible with ISO Class 4 (former Class 10). Can be used in the Pharmaceutical industry with optional stainless steel SAE 304 cart
- Designed for applications where finely pulverized dusts are to be recovered
- Single phase explosion proof/dust ignition proof motor
- Manual Filter Shaker (MFS) system
- For dry recovery only
- All stainless steel SAE 304 construction (except cart)
- Stainless steel cart available
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Static dissipative poly liner and clip for the easy and safe disposal of recovered materials - available
- Equipped with a 4-wheel cart and tool basket. Cart has static dissipative or conductive wheels
- Includes a complete static dissipative tool kit



Specifications

EXP1-20L (DT) RE HEPA (MFS)	110364B
Model Name	EXP1-20L (DT) RE HEPA (MFS)
Type (Powerhead)	Electric
TEFC Motor	Yes
Voltage	230 V
Hertz	50 Hz
Phase	Single
Wattage	1000 W
Power	1 kW
Amperage	4.5 A
Air Flow	224 m ³ /h
Vacuum Pressure	1550 mm H ₂ 0
Sound Level	78/85 dB(A)
Plug Type	Not Included
Suction Inlet	50 mm
Cart Type	Detachable Tank (DT)
Filter Cleaning	Manual Filter Shaker (MFS)
Dry Recovery - Tank	25 L
Length	66 cm
Width	56 cm
Height	109 cm
Weight (Vacuum Only)	45 kg.
Cord Length	15 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



HEPA Filter - Included



Main Cloth Filter, Static Dissipative - Included



Ø1.5 (Ø38mm) Static Dissipative Tools and Accessories - Included



Conductive Polyliner Recovery Bag - Optional

Website: http://www.tiger-vac.eu Email: info@tiger-vac.it